Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec AG20 conductive silver pen with micro tip

1.2 Relevant identified uses of the substance or mixture and uses advised against

For making grounding paths on SEM samples, repairing traces on circuit boards, making contact pads.

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano Tappersweg 91 2031ET Haarlem Netherlands

Tel: +31(0)85-2013155 E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Physical: Flammable liquid, category 2

Highly flammable liquid and vapour

Health: Aspiration irritation, category 1

Skin corrosion/irritation category 2

Eye irritation, category 2

Reproductive toxicity category 3 May cause drowsiness or dizziness

Environment: Chronic aquatic hazard category 1

Other hazards: None

Classification according to Regulation EC Nr. 1272/2008

F: HIGHLY FLAMMABLE

Xi: Irritant Xn: Harmful



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

Health: R36: Irritating to eyes

R38: Irritating to skin

R48/20: Harmful: danger of serious damage to health by prolonged exposure

through inhalation

R62 (3): Possible risk of impaired vertility

R63 (3): Possible risk of harm to the unborn child R67: Vapours may cause drowsiness and dizziness

Physical R11: Highly flammable

Environment: R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment

Other hazards: Not classified

2.2 Labeling elements

Labelling accordance to Regulation EC Nr. 1272/2008

Hazard pictogramm(s):









Signal word: Danger

Hazard statement(s): H225: Highly flammable liquid and vapour

H315: Causes skin irritation H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

H361d: Suspected of damage to the unborn child

H373: May cause damage to organs through prolonged or repeated

exposure

H410: Very toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention: P102: Keep out of reach of children

P 201: Obtain special instructions before use

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking P233: Keep container tightly closed

P260: Do not breath dust/fumes/gas/mist/vapours/spray

P264: Wash hand thouroughly after handling

P270: Do not eat, drink or smoke when using this product P 271: Use outdoors or in well ventilated area (fume hood)

P 273: Avoid release to the environment

P280: Wear protective gloves/protective clothing/eye protection/face

protection

Response: P301+P310: If swallowed: Immediately call a poison

Center/doctor/physician/first aider

P308+P313: If exposed or concerned: Get medical attention



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 Version: 2.0

P331: No NOT induce vomiting

P312: Call a poison center/doctor/physician/first aider if you feel unwell P370+378: In case of fire: Use alcohol resistant foam or protein foam for

extinction

P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses if easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical attention P302+P352: If on skin: Wash with plenty of water and soap.

P304+P340: If inhaled: Remove person to fresh air and keep comfortable for

breathing

P332+P313: If skin irritation occurs: Get medical attention

P362+P364: Take of contaminated clothing and wash before reuse

P391: Collect spillage

Storage: P403+P235: Store in a well-ventilated place. Keep cool

P405: Store locked up

Disposal: P501: Dispose of contents/container in accordance to local/regional/

international regulations

Supplemental hazard info: none

2.3 Other hazards

Skin dryness; repeated exposure may cause skin dryness or cracking

Section 3: Composition / information on components

3.1. Substances

Not applicable

3.2 Mixtures

1. CAS Nr 2. EC Nr 3. Index Nr 4. REACH No	% (weight)	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation Nr 1272/2008 [CLP]
108-88-3 203-625-9 601-021-00-3 01-2119471310-51-xxxx	12-14	toluene	R11R38R48/20R63 R65R67	Flam.Liq. 2, Repr. 2, Asp Tox. 1 STOT RE 2, Skin Irrit.2, STOT RE 3, H225, H361d, H304, H373, H315, H336(3)
7440-22-4 231-131-3 not available 01-2119555669-21-xxxx	45-50	silver	R52	Not applicable



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

110-43-0 203-767-1 606-024-00-3 01-2119902391-49-xxxx	2-4	Amyl/methyl ketone	R10R20/22	Flam. Liq. 3, Acute Tox, 4; H226, H332, H302
67-64-1 200-662-2 606-001-00-8 01-2119471330-49-xxxx	4-5	acetone	R11R36R66R67	Flam. Liq. 2, Eye Irri. 2, STOT SE 3; H225, H319, H336, EUH066
64-17-5 200-578-6 603-002-00-5 01-2119457610-43-xxxx	2-4	ethanol	R11	Flam. Liq. 2; H225
110-19-0 203-745-1 607-026-00-7 01-2119488971-22xxxx	2-4	Isobutyl acetate	R11R66	Flam. Liq. 2; H225,EUH066
123-86-4 204-658-1 607-025-00-1 01-2119485493-29-xxxx	8-10%	N-Butyl acetate	R10R66R67	Flam. Liq. 3; H225 STOT SE3, H336
141-78-6 205-500-4 607-022-00-5 01-2119475103-46-xxxx	1-2	Ethyl acetate	R11R36R66R67	Flam. Liq. 2, Eye Irri. 2, STOT SE 3; H225, H319, H336, EUH066
108-65-6 203-603-9 not available not available	0.1-1%	1-methoxyl-2- propanol acetate	R11	Flam.Liq. 3; H225

^{(*} Explanation notes: see section 16)

Section 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: Rinse cautiously with water for several minutes. If possible, remove contact

lenses. Continue rinsing.

Seek medical attention if irritation persists.

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists.

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention of ill effects occur

Ingestion: If swallowed, do not induce vomiting

Seek immediate medical advice



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS0015002520-01 **Version:** 2.0

If vomiting appears imminent or occurs hold patient's head down, lower than their

hips to help avoid possible aspiration of vomitus. Never give liquid to a person with reduced awareness

Give water to rinse out mouth, then provide water slowly as much as casually can

comfortably drink Avoid giving milk or oils Avoid giving alcohol

4.2. Important symptoms and effects, either immediate or delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to cough, drowsiness,

headaches and dizziness

Ingestion: May cause respiratory and digestive tract irritation

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Mildly irritating to skin

Symptoms: redness, irritation and dry skin

Eye contact: Irritating to eyes

Symptoms: redness, irritation and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment

General advise: If you feel unwell, seek medical advice; show product label if possible

If symptoms persist, always call a doctor

Section 5: Firefighting Measures

5.1. Extinguishing media

Use dry sand, graphite powder, dry sodium based extinguishers **Do not** use water, CO2, foam or halogenated fire extinguishing agents

5.2 Special hazards arising from the substance or mixture

The vapours are heavier than air and may accumulate in low-lying areas Produces CO and CO2

5.3 Advice to firefighters

In case of fire; do not breathe fumes
Wear self-contained breathing apparatus for fire fighting



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Avoid breathing fumes/vapours
Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment

Do not allow to enter public sewers and waterways

6.3 Methods and material for containment and clean up

Absorb spillage in suitable inert material
Clean up spills immediately
Avoid breathing vapours
Control personal contact with the substance, by using protective equipment
Collect spillage, absorbed spillage and wipes in a flammable waste container
Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

For further information see section 8

Section 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children
Keep away from sources of ignition
Do not breathe aerosols or vapours
Ensure adequate ventilation
Avoid contact with skin and eyes
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection
Have eyewash bottles available



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place

Store locked up Keep cool

7.3 Specific end uses(s)

Making grounding paths for SEM samples Repairing traces on circuit boards Making contact pads

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)

Ingredient	Material Name	Source	TWA	STEL	Peak	Notes
toluene	Toulene	UK	191mg/m3	384mg/m3	Not available	Skin
		EU	191mg/m3	384mg/m3	Not available	Skin
Amyl methyl	Heptan-2-one	UK	237mg/m3	475mg/m3	Not available	Skin
ketone		EU	238mg/m3	475mg/m3	Not available	Skin
acetone	Acetone	UK	1210mg/m3	3620mg/m3	Not available	Not available
		EU	1210mg/m3	Not available	Not available	Not available
ethanol	Ethanol	UK	1920mg/m3	Not available	Not available	Not available
Isobutyl acetate	Isobutyl acetate	UK	724mg/m3	903mg/m3	Not available	Not available
N-Butyl acetate	N-Butyl acetate	UK	150ppm	200mg/m3	Not available	Skin
ethyl acette	Ethyl acetate	UK	200ppm	400ppm	Not available	Not available
Silver flakes	Silver (metal) Ag	UK	0.1mg/m3	Not available	Not available	Not available
1-methyl-2-pro- panol acetate	1-methyl-2-pro- panol acetate	UK	50mg/m3	75 mg/m3	Not available	Not available

8.2 Exposure controls

Control procedures: Ensure adequate ventilation

Keep away from heat sources and ignition sources



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 Version: 2.0

Personal protection: Take precautions to avoid contact with eyes and skin when handling the products

Ensure adequate ventilation

Inhalation: In case of insufficient ventilation, wear suitable respiratory equipment:

Air purifying respirator with organic gas/vapour cartridge (type A)

Hands and skin: Wear suitable gloves against chemicals; recommended gloves:

Nitrile

Eyes: Wear safety goggles or full face protection

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Liquid

Colour: Metallic silver
Odour: Solvent

pH not applicable

Boiling point/range: 56°C

Flash point: -17°C (closed cup)

Evaporation rate: >1
Explosion limits: upper limit: 13%
lower limit: 1%

Vapour pressure: 68 kPa

Relative density: 1.8 g/cm3 @ 20°C **Solubility in water:** partly miscible

Auto-ignition: >315°C Viscosity: >34 cSt

9.2 Other information

VOC: 34% (603g/L)

Section 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purposes

10.2 Chemical stability

Stable at normal temperatures and pressures



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purposes

10.4 Conditions to avoid

Avoid overheating, ignition sources and incompatible substances

10.5 Incompitable materials

Strong oxidising agents, strong acids, strong bases

10.6 Hazardous decomposition products

CO, CO2 and smoke

Section 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Skin contact: Prolonged skin contact will result in defattening of the skin, leading to irritation and in

some cases to dermatitis

Eye contact: Irritation to eyes

Toxicological data:

Ingredient	Toxicity	Irritation
Toluene	Dermal (rabbit) LD: 12124mg/l	Eye (rabbit): 2mg/24h - severe
	Inhalation (rat) LC50: 49mg/l	Eye (rabbit): 100mg/30s - mild
	Oral (rat) LD50: 636 mg/kg	Skin (rabbit): 20mg/24h - moderate
Silver, metal	Oral (rat) LD50: >2000 mg/kg	Not available
Amyl methyl ketone	Dermal (rabbit) LD: 12600mg/l	Skin (rabbit): 14mg/24h - mild
	Inhalation (rat) LC50: 4000ppm/4h	
	Oral (rat) LD50: 1670 mg/kg	
Acetone	Dermal (rabbit) LD: 20000mg/l	Eye (human): 500ppm - irritant
	Inhalation (rat) LC50: 50.1mg/l/8h	Eye (rabbit): 20mg/24h - moderate



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

	Oral (rat) LD50: 5800 mg/kg	Skin (rabbit): 500mg/24hr - mild
ethanol	Dermal (rabbit) LD: 17100mg/l	Eye (rabbit): 500mg - severe
	Inhalation (rat) LC50: 64000ppm/4h	Eye (rabbit): 100mg/24h - moderate
	Oral (rat) LD50: 11872769 mg/kg	Skin (rabbit): 20mg/24hr - moderate
Isobutyl acetate	Dermal (rabbit) LD: >5000 mg/kg	moderate
	Oral (rat) LD50: 134000 mg/kg	Skin (rabbit): 500mg open mild
n-Butyl-acetate	Dermal (rabbit) LD: 14.080 mg/kg	Nil reported
	Inhalation (rat) LC50: 2000 ppm/4h	
	Oral (rat) LD50: 7400 mg/kg	
Ethyl acetate	Dermal (rabbit) LD: >18000mg/kg	Eye (human):400ppm
	Inhalation (rat) LC50: >6000ppm/6h	
	Oral (rat) LD50: >10170 mg/kg	
1-methyl-2-propanol-acetate	Dermal (rabbit) LD: 5000mg/kg	
	Oral (rat) LD50: 8532 mg/kg	
EM-Tec AG20 conductive silver pen	Not available	Not available

Section 12: Ecological information

12.1. Toxicity

Not available

12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence:Air
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
amyl methyl ketone	LOW	LOW
acetone	LOW (Half-life = 14 days)	Medium (Half-life = 116.25 days)
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
Isobutyl acetate	LOW	LOW
n-Butyl-acetate	LOW	LOW
Ethyl acetate	LOW (Half-life = 14 days)	LOW (Half-life = 14.71 days)
1-methoxy-2-propanol acetate	LOW	LOW



Regulation EC Nr. 1907/2006 Art.31

February 1st 2022

Date:

Product name: EM-Tec AG20 conductive silver pen

Document Nr.: SDS0015002520-01 **Version:** 2.0

12.3 Bioaccumulative potential

Ingredient	Bioaccumulation
toluene	LOW (BCF = 90)
amyl methyl ketone	LOW (logKOW = 1.98)
acetone	LOW (BCF = 90)
ethanol	LOW (logKOW = 0.31)
Methanol	LOW
Isobutyl acetate	LOW (logKOW = 1.78)
n-Butyl-acetate	LOW
Ethyl acetate	High (BCF = 90)
1-methoxy-2-propanol acetate	LOW

12.4 Mobility in soil

Ingredient	Bioaccumulation
toluene	LOW (KOC = 268)
amyl methyl ketone	LOW (KOC = 24)
acetone	HIGH(KOC = 1.981)
ethanol	HIGH (KOC = 1)
methanol	HIGH (KOC = 1)
Isobutyl acetate	LOW (KOC = 17.48)
n-Butyl-acetate	HIGH
Ethyl acetate	LOW (KOC = 6.131)
1-methoxy-2-propanol acetate	HIGH

12.5 Results of PBT and vPvB assessment

No information available

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Containers may still present a chemical hazard when empty

Do not discharge into drains or the environment, dispose to an authorised waste

collection point.

National regulations: Disposal should be in accordance with local, state or national legislation.

Section 14: Transport information

Labels required:



14.1. UN number

UN-number: 1263

14.2 UN proper shipping name

Proper shipping name: PAINT

14.3 Transport hazard class(es)

Class: 3
ADR/RID-Classification code: F1

14.4 Packing group

Packing: II
Limited Quantity 5L

14.5 Incompatable materials

ADR/RID- Environmentally hazardous: Not applicable

IMDG-Marine poluttant: Yes

IATA/ICAO-Environmentally hazardous: No relevant data

14.6 Special precautions for user

ADR/RID-Tunnelcode: (D/E) **IMDG-EMS**: F-E, S-E



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS0015002520-01 **Version:** 2.0

 IATA/ICAO-PAX:
 353

 IATA/ICAO-CAO:
 364

 IATA/ICAO-DGR:
 Y341

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UN-number: 1263

15.2 Chemical safety assessment

No information available

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Asp. Tox Aspiration hazard Carc. Carcinogenicity Exp. Exposure Flam. Flammable

GHS Global Harmonised System of Classification of Labelling Chemicals

Irrit. Irritant

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50% N/A Not applicable N/E Not estimated

PBT Persistent Bioaccumulative and Toxic

WEL Workplace Exposure Limit



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS0015002520-01 **Version:** 2.0

Repr. Reproductive toxitant

ROHS Restriction of Hazardous Substance
SEM Scanning Electron Microscope
STEL Short-Term Exposure Limit
STOT Specific Target Organ Toxicity

TCLo Lowest published toxic concentration

vPvB very Persistent and very Bioaccumulative

WEEE Waste Electrical and Electronic Equipment

DSD / DPD label elements





Full Text Risk and Hazard codes

H220 – Extremely flammable gas.

H226 - Flammable liquid and vapour.

H228 - Flammable solid

H301 – Toxic if swallowed.

H302 – Harmful if swallowed.

H304 - May be fatal id swallowed and enters airways.

H311 – Toxic in contact with skin.

H314 – Causes severe skin burn and eye damage.

H317 - May cause an allergic skin reaction.

H331 - Toxic if inhaled.

H332 - Harmful if inhaled.

H335 – May cause respiratory irritation.

H340 – May cause genetic defects.

H350 - May cause cancer.

H351 – Suspected of causing cancer.

H360 – May damage fertility or the unborn child.

H361 – Suspected of damaging fertility or the unborn child.

H362 – Mag cause harm to breast-fed children.

H370 – Causes damages to organs.

H371 – May cause damage to organs.

H372 – Causes damage to organs through prolonged or repeated exposure.

H400 – Very toxic to aquatic life.

H410 – Very toxic to aquatic life with long lasting effects.

H411 – Toxic to aquatic life with long lasting effects.

H413 – May cause long lasting harmful effects to aquatic life.

R10 - Flammable.

R20- Harmful by inhalation.

R20/22 - Harmful by inhalation and if swallowed.



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG20 conductive silver pen **Date:** February 1st 2022

Document Nr.: SDS0015002520-01 **Version:** 2.0

R36 – Irritating to eyes.

R37 – Irritating respiratory system.

R38 - Irritating to skin.

R52 - Harmful to aquatic organisms

R63 – Possible risk of harm to the unborn child.

R65 – Harmful – May cause long damage if swallowed

R66 – Repeated exposure may cause skin dryness and cracking.

Safety advice:

S02 - Keep out of reach of children.

S09 – Keep container in a well ventilated place.

S13 – Keep away from food, drink and animal feeding stuff.

S16 – Keep away from sources of ignition. No smoking.

S23 – Do not breath gas/fumes/vapour/spray.

S26 – In case of contact with eyes, rinse with plenty of water and seek medical help.

S281 – After contact with skin, wash immediately with detergent and plenty of waterways.

S29 – Do not empty in drains.

S33 – Take precautionary measures against static discharges.

S35 – This materials and its container must be disposed of in a safe way.

S36 – Wear suitable protective clothing.

S37 – Wear suitable gloves.

S38 – In case of insufficient ventilation, wear suitable respiratory equipment.

S39 - Wear eye / face protection.

S40 – In case of insufficient ventilation, wear suitable respiratory equipment.

S41 – In case of fire and/or explosion; DO NOT breathe fumes.

S43 - In case of fire use....

S45 – In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).

S46 – If swallowed, seek immediate medical advice and show label if possible.

S52 – Not recommended for interior use on large surfaces.

S53 – Avoid exposure – obtain special instructions before use.

S56 – Dispose of this materials and its container at hazardous or special waste collection point.

S57 – Use appropriate container to avoid environment contamination.

S61 – Avoid release to the environment

S63 – In case of accident by inhalation, remove casualty to fresh air and keep at rest.

S64 – If swallowed, rinse mouth with water (only if person is conscious)

This product should be stored, handled and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.

